



NO.	REV.	MODIFY NOTES	REVISED	DATE
1	A1	新版发行	Wanglong	09.02.18

SPECIFICATIONS

Current Rating : 1.5AMP

Operation Temperature : -40°C to +105°C

Contact Resistance : 20mΩ Max.

Insulation Resistance : 1000MΩ Min

Withstanding Voltage : AC 500V

Insulator Material : Polyester (U194V-0)
Standard: Nylon-66

Contact Material : Phosphor Bronze

Contact Plating : Au or Over 50 U" Ni

TOLERANCE:		NT	東莞市安拓電子有限公司	
X	±XXX		DONGGUAN ANTUO electronic co.,LTD	
X	±0.20		地址: 廣東省東莞市長安鎮柳屋第一工業區	
.XX	±0.10		電話: +0769-82716236 傳真: +0769-82716087	
ANG.		2.00mm Female Header, Dual Row, Straight(PC104)		
TITLE:		AT-09020087		THIRD ANGLE PROJECTION
DWG NO.				

SIGNATURE		DATE		CODE NO.	
Wanglong		2009.02.18		JW00	
CH.K.		2009.02.18		CUS. NO.	
Summer		2009.02.18		SCALE	
A P P.				UNIT	
				PAGE	
				1/1	